

## 6378AB-C

## **SOFT SERVE FREEZER**

Two Flavor, Floor, Digital Controls









# Most Compact & Powerful High capacity 2-flavor floor model with Auto-Pasteurization and intelligent controls

#### **Auto-Pasteurization**

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

#### **Digital Control and Display**

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

#### **Operation Logging**

Logs every operation and error to provide history and data for easy troubleshooting

#### **Auto Programming**

Allows automatic switching of operation modes based on preset scheduels

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato with desire for significant reduction in labor cost of cleaning.

#### **Hopper Agitators**

Maintain product consistency and prevent product separation

#### **Defrost for Cleaning**

Increases efficiency during cleaning by heating frozen product in cylinder

#### **Direct Drive Transmission**

Eliminates consumable moving parts and increases transmission efficiency

#### **Safety Protections**


- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- $\bullet \ \ \mathsf{High}\,\mathsf{pressure}\,\mathsf{switch}\,\mathsf{to}\,\mathsf{prevent}\,\mathsf{compressor}\,\mathsf{overheating}$
- Thermal overload to protect from motor overheating






# 6378AB-C

## **SOFT SERVE FREEZER**





#### **SPECIFICATIONS**

Flavors	2 + Twist
Freezing Cylinders	2 x 3.2L / 3.4qt
Mix Hoppers	2 x 12L / 12.7qt
Output Capacity (80 grams)	800 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb
Net	312 / 693
Shipping	331/736
Volume	1.09 CBM / 38.62 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	552 / 21.7	710 / 28.0
Depth	820/32.3	890/35.0
Height	1563 / 61.5	1730 / 68.1

Electrical	MFS	MCA	Power(kW)
380-415/50/3	30	20	5.0
208-230/60/3	40	30	5.0

 $\boldsymbol{\cdot}$  Above specifications are subject to change without notice

#### **FEATURES** Control Systems Two, Digital Refrigerated Hoppers Hopper Agitator Temperature Display Standby Mode Auto Clsoing Dispensing Valves Dispensing Speed Control Low Mix Indicator Light Low Mix Indicator Alarm Low Temperature Protection Motor Amperage Protection High Pressure Protection Thermal Overload Protection Soft Start

AVAILABLE OPTIONS	
Water Cooled	$\checkmark$
Top Air Discharge Chute	
Spinner	$\checkmark$
Custom Branding	